


VE

Endstück für Unterflurkanal



| Standardausführung |          |                            |                            | Sendzimir verzinkt            |                            |        |              |       |         |
|--------------------|----------|----------------------------|----------------------------|-------------------------------|----------------------------|--------|--------------|-------|---------|
| HD                 | Referenz | <div>↕</div> <div>mm</div> | <div>↔</div> <div>mm</div> | <div>→  ←</div> <div>mm</div> | <div>↔</div> <div>mm</div> | kg/stk | <div>📦</div> | Lager | Einheit |
| -                  | VE28.170 | 30                         | 165                        |                               |                            | 0,080  | 1            |       | STK     |
| -                  | VE28.250 | 30                         | 245                        |                               |                            | 0,110  | 1            |       | STK     |
| -                  | VE28.350 | 30                         | 345                        |                               |                            | 0,160  | 1            |       | STK     |
| -                  | VE38.170 | 40                         | 165                        |                               |                            | 0,100  | 1            |       | STK     |
| -                  | VE38.250 | 40                         | 245                        |                               |                            | 0,140  | 1            |       | STK     |
| -                  | VE38.350 | 40                         | 345                        |                               |                            | 0,180  | 1            |       | STK     |
| -                  | VE48.170 | 50                         | 165                        |                               |                            | 0,110  | 1            |       | STK     |
| -                  | VE48.250 | 50                         | 245                        |                               |                            | 0,160  | 1            |       | STK     |
| -                  | VE48.350 | 50                         | 345                        |                               |                            | 0,220  | 1            |       | STK     |

Geprüft nach EN 50085-2-2.