


I6LOMEGA150

Bracket / Ceiling profile



| Standard finish |  | Stainless Steel 316 |  |
|-----------------|--|---------------------|--|
|                 |  | Max. load (in daN)  |  |
| 100             |  | 110                 |  |
| 150             |  | 100                 |  |
| 200             |  | 90                  |  |
| 300             |  | 70                  |  |
| 400             |  | 50                  |  |
| 500             |  | 40                  |  |
| 600             |  | 30                  |  |

| HD | Reference       | <div>↕</div> <div>mm</div> | <div>↔</div> <div>mm</div> | <div>→  ←</div> <div>mm</div> | <div>↔</div> <div>mm</div> | kg/stk | <div>📦</div> | Stock | Unit |
|----|-----------------|----------------------------|----------------------------|-------------------------------|----------------------------|--------|--------------|-------|------|
| -  | I6LOMEGA150.100 | 145                        | 145                        |                               |                            | 0,300  | 12           | X     | STK  |
| -  | I6LOMEGA150.150 | 145                        | 195                        |                               |                            | 0,320  | 12           | X     | STK  |
| -  | I6LOMEGA150.200 | 145                        | 245                        |                               |                            | 0,340  | 12           | X     | STK  |
| -  | I6LOMEGA150.300 | 145                        | 345                        |                               |                            | 0,490  | 6            | X     | STK  |
| -  | I6LOMEGA150.400 | 145                        | 445                        |                               |                            | 0,540  | 6            | X     | STK  |
| -  | I6LOMEGA150.500 | 145                        | 545                        |                               |                            | 0,640  | 6            | X     | STK  |
| -  | I6LOMEGA150.600 | 145                        | 645                        |                               |                            | 0,770  | 6            | X     | STK  |

Use the I6VOMEGA to avoid compression of the profiles.

Pickled and passivated.