

KLLSB.45

Internal riser 45° for KLL



Standard finish		Pre-galvanised							
Optional finish		Hot-dip galvanised							
HD	Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
HD	KLLSB60.150.45	60	143			1,146	1		STK
HD	KLLSB60.200.45	60	193			1,222	1		STK
HD	KLLSB60.300.45	60	293			1,373	1		STK
HD	KLLSB60.400.45	60	393			1,524	1		STK
HD	KLLSB60.450.45	60	443			1,600	1		STK
HD	KLLSB60.500.45	60	493			1,676	1		STK
HD	KLLSB60.600.45	60	593			1,826	1		STK
HD	KLLSB110.150.45	110	145			2,201	1		STK
HD	KLLSB110.200.45	110	195			2,066	1		STK
HD	KLLSB110.300.45	110	295			2,217	1		STK
HD	KLLSB110.400.45	110	395			2,369	1		STK
HD	KLLSB110.450.45	110	445			2,444	1		STK
HD	KLLSB110.500.45	110	495			2,520	1		STK
HD	KLLSB110.600.45	110	595			2,671	1		STK

Minimum number bolts and nuts VM6.10: 8 pieces.

Toothed round head bolt / flange nut
VM