

KLLSB

Internal riser for KLL



Fix with:



Toothed round head bolt / flange nut
VM

Standard finish		Pre-galvanised							
Optional finish		Hot-dip galvanised							
HD	Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
HD	KLLSB60.150	60	146			1,528	1		STK
HD	KLLSB60.200	60	196			1,629	1		STK
HD	KLLSB60.300	60	296			1,830	1		STK
HD	KLLSB60.400	60	396			2,032	1		STK
HD	KLLSB60.450	60	443			2,133	1		STK
HD	KLLSB60.500	60	496			2,234	1		STK
HD	KLLSB60.600	60	596			2,435	1		STK
HD	KLLSB110.150	110	145			2,934	1		STK
HD	KLLSB110.200	110	196			2,755	1		STK
HD	KLLSB110.300	110	296			2,956	1		STK
HD	KLLSB110.400	110	396			3,158	1		STK
HD	KLLSB110.450	110	445			3,259	1		STK
HD	KLLSB110.500	110	496			3,360	1		STK
HD	KLLSB110.600	110	596			3,561	1		STK
HD	KLLSB110.750	110	750			3,863	1		STK
HD	KLLSB110.900	110	900			4,165	1		STK

Minimum number bolts and nuts VM6.10: 8 pieces.