

KLLSB

Internal riser for KLL



Fix with:



Toothed round head bolt / flange nut
VM

Standard finish		Pre-galvanised							
Optional finish		Hot-dip galvanised							
HD Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit	
HD KLLSB60.150	60	146			1,528	1		STK	
HD KLLSB60.200	60	196			1,629	1		STK	
HD KLLSB60.300	60	296			1,830	1		STK	
HD KLLSB60.400	60	396			2,032	1		STK	
HD KLLSB60.450	60	443			2,133	1		STK	
HD KLLSB60.500	60	496			2,234	1		STK	
HD KLLSB60.600	60	596			2,435	1		STK	
- KLLSB60.750	60	750	1,25		2,933	1		STK	
- KLLSB60.800	60	800	1,25		3,049	1		STK	
- KLLSB60.900	60	900	1,25		3,282	1		STK	
HD KLLSB110.150	110	145			2,934	1		STK	
HD KLLSB110.200	110	196			2,755	1		STK	
HD KLLSB110.300	110	296			2,956	1		STK	
HD KLLSB110.400	110	396			3,158	1		STK	
HD KLLSB110.450	110	445			3,259	1		STK	
HD KLLSB110.500	110	496			3,360	1		STK	
HD KLLSB110.600	110	596			3,561	1		STK	
HD KLLSB110.750	110	750			3,863	1		STK	
- KLLSB110.800	110	800	1,25		4,017	1		STK	
HD KLLSB110.900	110	900			4,165	1		STK	
- ZMKLLSB60.150	60	150	1,25		1,539	1		STK	
- ZMKLLSB60.200	60	200	1,25		1,655	1		STK	
- ZMKLLSB60.300	60	300	1,25		1,887	1		STK	
- ZMKLLSB60.400	60	400	1,25		2,120	1		STK	
- ZMKLLSB60.450	60	450	1,25		2,236	1		STK	
- ZMKLLSB60.500	60	500	1,25		2,352	1		STK	
- ZMKLLSB60.600	60	600	1,25		2,584	1		STK	
- ZMKLLSB60.750	60	750	1,25		2,933	1		STK	
- ZMKLLSB60.800	60	800	1,25		3,049	1		STK	
- ZMKLLSB60.900	60	900	1,25		3,282	1		STK	
- ZMKLLSB110.150	110	150	1,25		2,506	1		STK	
- ZMKLLSB110.200	110	200	1,25		2,623	1		STK	
- ZMKLLSB110.300	110	300	1,25		2,855	1		STK	
- ZMKLLSB110.400	110	400	1,25		3,087	1		STK	
- ZMKLLSB110.450	110	450	1,25		3,204	1		STK	
- ZMKLLSB110.500	110	500	1,25		3,320	1		STK	
- ZMKLLSB110.600	110	600	1,25		3,552	1		STK	
- ZMKLLSB110.750	110	750	1,25		3,901	1		STK	
- ZMKLLSB110.800	110	800	1,25		4,017	1		STK	
- ZMKLLSB110.900	110	900	1,25		4,249	1		STK	

Minimum number bolts and nuts VM6.10: 8 pieces.