


KLLVB

External riser for KLL



Fix with:



Toothed round head bolt / flange nut
VM

Standard finish		Pre-galvanised							
Optional finish		Hot-dip galvanised							
HD Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit	
HD KLLVB60.150	60	146			1,528	1		STK	
HD KLLVB60.200	60	196			1,629	1		STK	
HD KLLVB60.300	60	296			1,830	1		STK	
HD KLLVB60.400	60	396			2,032	1		STK	
HD KLLVB60.450	60	443			2,133	1		STK	
HD KLLVB60.500	60	496			2,234	1		STK	
HD KLLVB60.600	60	596			2,435	1		STK	
- KLLVB60.750	60	750	1,25		2,501	1		STK	
- KLLVB60.800	60	800	1,25		2,588	1		STK	
- KLLVB60.900	60	900	1,25		2,762	1		STK	
HD KLLVB110.150	110	145			2,934	1		STK	
HD KLLVB110.200	110	196			2,755	1		STK	
HD KLLVB110.300	110	296			2,956	1		STK	
HD KLLVB110.400	110	396			3,158	1		STK	
HD KLLVB110.450	110	445			3,259	1		STK	
HD KLLVB110.500	110	496			3,360	1		STK	
HD KLLVB110.600	110	596			3,561	1		STK	
HD KLLVB110.750	110	750			3,863	1		STK	
- KLLVB110.800	110	800	1,25		3,549	1		STK	
HD KLLVB110.900	110	900			4,165	1		STK	
- ZMKLLVB60.150	60	150	1,25		1,455	1		STK	
- ZMKLLVB60.200	60	200	1,25		1,542	1		STK	
- ZMKLLVB60.300	60	300	1,25		1,716	1		STK	
- ZMKLLVB60.400	60	400	1,25		1,891	1		STK	
- ZMKLLVB60.450	60	450	1,25		1,978	1		STK	
- ZMKLLVB60.500	60	500	1,25		2,065	1		STK	
- ZMKLLVB60.600	60	600	1,25		2,239	1		STK	
- ZMKLLVB60.750	60	750	1,25		2,501	1		STK	
- ZMKLLVB60.800	60	800	1,25		2,588	1		STK	
- ZMKLLVB60.900	60	900	1,25		2,762	1		STK	
- ZMKLLVB110.150	110	150	1,25		2,416	1		STK	
- ZMKLLVB110.200	110	200	1,25		2,503	1		STK	
- ZMKLLVB110.300	110	300	1,25		2,677	1		STK	
- ZMKLLVB110.400	110	400	1,25		2,851	1		STK	
- ZMKLLVB110.450	110	450	1,25		2,939	1		STK	
- ZMKLLVB110.500	110	500	1,25		3,026	1		STK	
- ZMKLLVB110.600	110	600	1,25		3,200	1		STK	
- ZMKLLVB110.750	110	750	1,25		3,462	1		STK	
- ZMKLLVB110.800	110	800	1,25		3,549	1		STK	
- ZMKLLVB110.900	110	900	1,25		3,723	1		STK	

Minimum number bolts and nuts VM6.10: 8 pieces.