


KLLX

Cross-over for KLL



Standard finish	Pre-galvanised					
Optional finish	Hot-dip galvanised					

	150	200	300	400	500	600
A	1021	1071	1171	1271	1371	1471

Fix with:



Toothed round head bolt / flange nut
VM

HD Reference	mm	mm	mm	mm	kg/stk	Stock	Unit
HD KLLX60.150	60	141			3,131	1	STK
HD KLLX60.200	60	191			3,232	1	STK
HD KLLX60.300	60	291			4,421	1	STK
HD KLLX60.400	60	391			4,875	1	STK
HD KLLX60.450	60	443			5,102	1	STK
HD KLLX60.500	60	491			5,329	1	STK
HD KLLX60.600	60	591			5,782	1	STK
- KLLX60.750	60	750	1,25		8,530	1	STK
- KLLX60.800	60	800	1,25		8,890	1	STK
- KLLX60.900	60	900	1,25		9,611	1	STK
HD KLLX110.150	110	145			4,537	1	STK
HD KLLX110.200	110	195			4,796	1	STK
HD KLLX110.300	110	295			5,985	1	STK
HD KLLX110.400	110	395			6,439	1	STK
HD KLLX110.450	110	445			6,666	1	STK
HD KLLX110.500	110	495			6,893	1	STK
HD KLLX110.600	110	595			7,346	1	STK
- KLLX110.800	110	800	1,25		10,408	1	STK
HD KLLX110.900	110	900			9,546	1	STK
- ZMKLLX60.150	60	150	1,25		3,985	1	STK
- ZMKLLX60.200	60	200	1,25		4,258	1	STK
- ZMKLLX60.300	60	300	1,25		4,965	1	STK
- ZMKLLX60.400	60	400	1,25		5,570	1	STK
- ZMKLLX60.450	60	450	1,25		5,872	1	STK
- ZMKLLX60.500	60	500	1,25		6,451	1	STK
- ZMKLLX60.600	60	600	1,25		7,113	1	STK
- ZMKLLX60.750	60	750	1,25		8,530	1	STK
- ZMKLLX60.800	60	800	1,25		8,890	1	STK
- ZMKLLX60.900	60	900	1,25		9,611	1	STK
- ZMKLLX110.150	110	150	1,25		5,502	1	STK
- ZMKLLX110.200	110	200	1,25		5,775	1	STK
- ZMKLLX110.300	110	300	1,25		6,483	1	STK
- ZMKLLX110.400	110	400	1,25		7,087	1	STK
- ZMKLLX110.450	110	450	1,25		7,390	1	STK
- ZMKLLX110.500	110	500	1,25		7,969	1	STK
- ZMKLLX110.600	110	600	1,25		8,631	1	STK
- ZMKLLX110.750	110	750	1,25		10,047	1	STK
- ZMKLLX110.800	110	800	1,25		10,408	1	STK

HD	Reference	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Unit
-	ZMKLLX110.900	110	900	1,25		11,129	1		STK

Minimum number bolts and nuts VM6.10: 16 pieces.