KLZX
Cross-over for KLZ

Fix with:



Flange nut (DIN 6923)
RM



Round head square neck bolt (DIN 603)
RBK

Standard finish	Pre-galvanised

	200	300	400	500	600
A	1962	2062	2162	2262	2362

HD	Reference	↕ mm	↔ mm	→‖← mm	⇄ mm	kg/stk	⬚	Stock	Unit
-	**KLZX150**	150	150			18,096	1		STK
-	**KLZX200**	150	208			18,006	1		STK
-	**KLZX300**	150	308			19,269	1		STK
-	**KLZX400**	150	408			20,406	1		STK
-	**KLZX500**	150	508			21,544	1		STK
-	**KLZX600**	150	608			24,771	1		STK
-	**KLZX800**	150	800			27,307	1		STK
-	**KLZX1000**	150	1000			30,579	1		STK
-	**ZMKLZX150**		150			18,096	1		STK
-	**ZMKLZX200**	150	208			18,006	1		STK
-	**ZMKLZX300**	150	308			19,269	1		STK
-	**ZMKLZX400**	150	408			20,406	1		STK
-	**ZMKLZX500**	150	508			21,544	1		STK
-	**ZMKLZX600**	150	608			24,771	1		STK
-	**ZMKLZX800**		800			27,307	1		STK
-	**ZMKLZX1000**		1000			30,579	1		STK
-	**PEKLZX150**	150	150			18,096	1		STK
-	**PEKLZX800**	150	800			27,307	1		STK
-	**PEKLZX1000**	150	1000			30,579	1		STK

Minimum number bolts and nuts: 16 pieces. Cross-over with a width of 900 and larger must be assembled on-site because they are too large to ship. That is why they are supplied with bolts and nuts (M6) for the assembly of the cross-over.