

**SLOS**  
**Partition**




Standard finish Pre-galvanised

Optional finish

| HD | Reference          | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/m  | 📦   | Stock | Unit |
|----|--------------------|---------|---------|------------|---------|-------|-----|-------|------|
| -  | <b>SLOS35</b>      | 28      |         |            | 3000    | 0,330 | 150 | X     | M    |
| -  | <b>SLOS60</b>      | 53      |         |            | 3000    | 0,511 | 120 | X     | M    |
| -  | <b>SLOS60.2000</b> | 53      |         |            | 1900    | 0,793 | 520 |       | M    |
| -  | <b>SLOS85</b>      | 78      |         |            | 3000    | 0,680 | 60  | X     | M    |
| -  | <b>SLOS110</b>     | 103     |         |            | 3000    | 0,820 | 30  | X     | M    |
| -  | <b>ZMSLOS35</b>    | 28      |         |            | 3000    | 0,257 | 150 | X     | M    |
| -  | <b>ZMSLOS60</b>    | 60      |         |            | 3000    | 0,397 | 120 | X     | M    |
| -  | <b>ZMSLOS85</b>    | 78      |         |            | 3000    | 0,529 | 60  |       | M    |
| -  | <b>ZMSLOS110</b>   | 103     |         |            | 3000    | 0,638 | 30  | X     | M    |

**Fix with:**



Toothed round head bolt  
RB

Sliding nut for supporting profile  
PNP06-  
PNP12A

Fixing set: 1 per meter.