

# OVG

## Open flush floor trunking



Ideal for frequent addition or removal of cables. For both new constructions and renovations.

| HD | Reference       | ↕<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/m   | 📦  | Stock | Unit |
|----|-----------------|---------|---------|------------|---------|--------|----|-------|------|
| -  | <b>OVG250.3</b> |         | 250     |            | 2400    | 9,406  | 24 | X     | M    |
| -  | <b>OVG350.3</b> |         | 350     |            | 2400    | 11,986 | 24 | X     | M    |
| -  | <b>OVG450.4</b> |         | 450     |            | 2400    | 19,228 | 24 | X     | M    |

Tested according EN 50085-2-2.

- Used in screeded floors to be finished with carpet or vinyl.
- Levelling range: 55 to 110 mm.
- Hinged covers can be mounted from levelling height 70 mm.
- Universal side for all levelling heights.
- Straightforward assembly of accessories with plastic corner connector.

Each flush floor trunking comes standard with the following products:

- 2 Extrusion profile (OVGP)
- 2 Universal sides (OVGZ)
- 3 Cross bars (OVGTR)
- 2 Carpet borders (OVGTAP)\*
- 3 Sealed covers (DOVG)
- 6 Levelling pieces
- 12 Taperedhead metal screws (ST48x25)
- 6 Screed anchor (OVGAN)
- 12 Tapered head bolts (BZ5.16)
- 6 Levelling screws
- 2 Baseplates (OVGVST)
- 4x ST48x22

\* Gauge of OVG TAP depends on the gauge of the cover.