


HSMES

Single ceiling profile



Ceiling profile: MP41.41S  
Welded headplate: 135x135 mm

| Standard finish |                  | Electro zinc-plated        |                            |                               |                            |        |              |       |      |
|-----------------|------------------|----------------------------|----------------------------|-------------------------------|----------------------------|--------|--------------|-------|------|
| Optional finish |                  | Hot-dip galvanised         |                            |                               |                            |        |              |       |      |
| HD              | Reference        | <div>↕</div> <div>mm</div> | <div>↔</div> <div>mm</div> | <div>→  ←</div> <div>mm</div> | <div>↔</div> <div>mm</div> | kg/stk | <div>📦</div> | Stock | Unit |
| HD              | <b>HSMES200</b>  | 200                        | 41                         |                               |                            | 1,020  | 20           | X     | STK  |
| HD              | <b>HSMES300</b>  | 300                        | 41                         |                               |                            | 1,280  | 1            | X     | STK  |
| HD              | <b>HSMES400</b>  | 400                        | 41                         |                               |                            | 1,530  | 1            | X     | STK  |
| HD              | <b>HSMES500</b>  | 500                        | 41                         |                               |                            | 1,790  | 1            | X     | STK  |
| HD              | <b>HSMES600</b>  | 600                        | 41                         |                               |                            | 2,050  | 1            | X     | STK  |
| HD              | <b>HSMES800</b>  | 800                        | 41                         |                               |                            | 2,570  | 1            | X     | STK  |
| HD              | <b>HSMES1000</b> | 1000                       | 41                         |                               |                            | 3,090  | 1            | X     | STK  |
| HD              | <b>HSMES1200</b> | 1200                       | 41                         |                               |                            | 3,600  | 1            | X     | STK  |
| HD              | <b>HSMES1500</b> | 1500                       | 41                         |                               |                            | 4,380  | 1            | X     | STK  |

Also applicable for double mounting.  
Use sliding nut PNP10 and hexagonal bolt B10.30.  
Protection cap in yellow PVC: DOP41.41.