I6KLM100
Cable ladder height 100

Cable ladder for large support distances up to 8 metres
Perforated C rungs 41 x 21

Standard finish								Stainless Steel 316	
HD	Reference	↕ mm	↔ mm	→‖← mm	⇄ mm	kg/m	📦	Stock	Unit
-	**I6KLM100.150**	100	168	1,5 MM	6000	5,135	60		M
-	**I6KLM100.200**	100	218	1,5 MM	6000	5,263	60		M
-	**I6KLM100.300**	100	318	1,5 MM	6000	5,519	60		M
-	**I6KLM100.400**	100	418	1,5 MM	6000	5,775	60		M
-	**I6KLM100.450**	100	468	1,5 MM	6000	5,903	60		M
-	**I6KLM100.500**	100	518	1,5 MM	6000	6,031	60		M
-	**I6KLM100.600**	100	618	1,5 MM	6000	6,287	60		M
-	**I6KLM100.750**	100	768	1,5 MM	6000	6,671	60		M
-	**I6KLM100.800**	100	818	1,5 MM	6000	6,799	60		M
-	**I6KLM100.900**	100	918	1,5 MM	6000	7,055	60		M
-	**I6KLM100.1000**	100	1018	1,5 MM	6000	7,311	60		M

CHARACTERISTICS
-strong
- usable inner height 102 mm, ideal for large diameter cables
- no further coupling holes are required if the cable ladder is cut
- no joiners are required to attach accessories such as bends, tees etc.
- rungs are perforated to enable efficient attachment of cables
- partition (I6SLOS60) can be fixed to the cable ladder with a sliding nut (I6PNP06) and pan head bolt (I6RB6.20).

TECHNICAL INFORMATION
Side walls are constructed from S profile with a return flange and are continuously perforated
- C-profile rungs are fixed at 250 mm intervals.
- rungs are mechanically attached to the side wall of the cable ladder.
- rungs are alternately placed with openings upwards and downwards.

Pickled and passivated.