

LOMEGACLU150

Wall bracket universal



|                 |                    |
|-----------------|--------------------|
| Standard finish | Pre-galvanised     |
| Optional finish | Hot-dip galvanised |

|                  | Max. load (in daN) |
|------------------|--------------------|
| LOMEGACLU150.100 | 110                |
| LOMEGACLU150.150 | 100                |
| LOMEGACLU150.200 | 90                 |
| LOMEGACLU150.250 | 80                 |
| LOMEGACLU150.300 | 70                 |
| LOMEGACLU150.400 | 50                 |
| LOMEGACLU150.500 | 40                 |
| LOMEGACLU150.600 | 30                 |

| HD | Reference               | ↑↓<br>mm | ↔<br>mm | →  ←<br>mm | ↔<br>mm | kg/stk | 📦  | Stock | Unit |
|----|-------------------------|----------|---------|------------|---------|--------|----|-------|------|
| HD | <b>LOMEGACLU150.100</b> | 145      | 155     |            |         | 0,300  | 12 | X     | STK  |
| HD | <b>LOMEGACLU150.150</b> | 145      | 185     |            |         | 0,320  | 12 | X     | STK  |
| HD | <b>LOMEGACLU150.200</b> | 145      | 235     |            |         | 0,340  | 12 | X     | STK  |
| HD | <b>LOMEGACLU150.250</b> | 145      | 285     |            |         | 0,450  | 12 | X     | STK  |
| HD | <b>LOMEGACLU150.300</b> | 145      | 335     |            |         | 0,490  | 12 | X     | STK  |
| HD | <b>LOMEGACLU150.400</b> | 145      | 435     |            |         | 0,540  | 6  | X     | STK  |
| HD | <b>LOMEGACLU150.500</b> | 145      | 535     |            |         | 0,710  | 6  | X     | STK  |
| HD | <b>LOMEGACLU150.600</b> | 145      | 635     |            |         | 0,770  | 6  | X     | STK  |

Fixing of the cable tray by VM6.20.  
Use the VOMEGA to avoid compression of the profile.  
Max. load (in daN): uniformly distributed over complete width of cantilever brackets.

Do not use with: VFUL30.065, VFUL35.150, VFU35.150, VFUL 60.050.