

KLLB.45

Courbe horizontale à 45° pour KLL



A fixer avec:



Boulon et écrou autobloquant
VM

Exec. Std.		Sendzimir							
Mat. Opt.		Galvanisé à chaud							
HD	Référence	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
HD	KLLB60.150.45	60	143			1,244	1		STK
HD	KLLB60.200.45	60	193			1,424	1		STK
HD	KLLB60.300.45	60	293			1,781	1		STK
HD	KLLB60.400.45	60	393			2,139	1		STK
HD	KLLB60.450.45	60	443			2,318	1		STK
HD	KLLB60.500.45	60	493			2,497	1		STK
HD	KLLB60.600.45	60	593			2,855	1		STK
-	KLLB60.750.45	60	750	1,25		2,842	1		STK
-	KLLB60.900.45	60	900	1,25		3,283	1		STK
-	KLLB60.800.45	60	800	1,25		2,989	1		STK
HD	KLLB110.150.45	110	145			2,299	1		STK
HD	KLLB110.200.45	110	195			2,120	1		STK
HD	KLLB110.300.45	110	295			2,538	1		STK
HD	KLLB110.400.45	110	395			2,955	1		STK
HD	KLLB110.450.45	110	445			3,164	1		STK
HD	KLLB110.500.45	110	495			3,374	1		STK
HD	KLLB110.600.45	110	595			3,791	1		STK
HD	KLLB110.750.45	110	750			4,418	1		STK
-	KLLB110.800.45	110	800	1,25		3,810	1		STK
HD	KLLB110.900.45	110	900			5,045	1		STK
-	ZMKLLB60.150.45	60	150	1,25		1,075	1		STK
-	ZMKLLB60.200.45	60	200	1,25		1,223	1		STK
-	ZMKLLB60.300.45	60	300	1,25		1,517	1		STK
-	ZMKLLB60.400.45	60	400	1,25		1,811	1		STK
-	ZMKLLB60.450.45	60	450	1,25		1,958	1		STK
-	ZMKLLB60.500.45	60	500	1,25		2,106	1		STK
-	ZMKLLB60.600.45	60	600	1,25		2,400	1		STK
-	ZMKLLB60.750.45	60	750	1,25		2,842	1		STK
-	ZMKLLB60.800.45	60	800	1,25		2,989	1		STK
-	ZMKLLB60.900.45	60	900	1,25		3,283	1		STK
-	ZMKLLB110.150.45	110	150	1,25		1,647	1		STK
-	ZMKLLB110.200.45	110	200	1,25		1,814	1		STK
-	ZMKLLB110.300.45	110	300	1,25		2,147	1		STK
-	ZMKLLB110.400.45	110	400	1,25		2,479	1		STK
-	ZMKLLB110.450.45	110	450	1,25		2,646	1		STK
-	ZMKLLB110.500.45	110	500	1,25		2,812	1		STK
-	ZMKLLB110.600.45	110	600	1,25		3,145	1		STK
-	ZMKLLB110.750.45	110	750	1,25		3,644	1		STK
-	ZMKLLB110.900.45	110	900	1,25		4,143	1		STK
-	ZMKLLB110.800.45	110	800	1,25		3,810	1		STK

Nombre minimal des boulons et des écrous VM6.10: 8 pièces.