


# SBCL

## Courbe concave VI à 90° encliquetable



Encliquetable avec chemin de câbles KBSC60, KBS60 et KBSI60

Exec. Std.

Sendzimir

Mat. Opt.

HD	Référence	↕ mm	↔ mm	→  ← mm	↔↔ mm	kg/stk	📦	Magasin	Unité
-	<b>SBCL90.60.050</b>	60	50			0,550	1	X	STK
-	<b>SBCL90.60.075</b>	60	75			0,650	1		STK
-	<b>SBCL90.60.100</b>	60	100			0,730	1	X	STK
-	<b>SBCL90.60.150</b>	60	150			0,880	1	X	STK
-	<b>SBCL90.60.200</b>	60	200			1,000	1	X	STK
-	<b>SBCL90.60.300</b>	60	300			1,180	1	X	STK
-	<b>SBCL90.60.400</b>	60	400			1,430	1	X	STK
-	<b>SBCL90.60.500</b>	60	500			1,900	1	X	STK
-	<b>SBCL90.60.600</b>	60	600			2,150	1	X	STK
-	<b>ZMSBCL90.60.050</b>	60	50			0,55	1	X	STK
-	<b>ZMSBCL90.60.075</b>	60	75			0,65	1		STK
-	<b>ZMSBCL90.60.100</b>	60	100			0,73	1	X	STK
-	<b>ZMSBCL90.60.150</b>	60	150			0,88	1	X	STK
-	<b>ZMSBCL90.60.200</b>	60	200			1	1	X	STK
-	<b>ZMSBCL90.60.300</b>	60	300			1,18	1	X	STK
-	<b>ZMSBCL90.60.400</b>	60	400			1,43	1	X	STK
-	<b>ZMSBCL90.60.500</b>	60	500			1,9	1	X	STK
-	<b>ZMSBCL90.60.600</b>	60	600			2,15	1	X	STK

Ouverture pour blocage supplémentaire par 4x VM6.10.  
Ouvertures prévues pour montage d'un couvercle.  
Uniquement disponible en hauteur de 60 mm.