

VH

Courbe réglable

Courbe réglable entre 90° et 180°

Exec. Std.

Sendzimir


Mat. Opt.



A fixer avec:



Boulon et écrou
autobloquant
VM



Écrou
autobloquant et
boulon à collet
VMK

HD	Référence	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Magasin	Unité
-	VH60.050	60	50			0,448	1		STK
-	VH60.075	60	75			0,486	1	X	STK
-	VH60.100	60	100			0,533	1	X	STK
-	VH60.150	60	150			0,659	1	X	STK
-	VH60.200	60	200			0,824	1	X	STK
-	VH60.300	60	300			1,385	1	X	STK
-	VH60.400	60	400			2,042	1	X	STK
-	VH60.500	60	500			2,913	1	X	STK
-	VH60.600	60	600			3,938	1	X	STK
-	ZMVH60.050	60	50			0,448	1		STK
-	ZMVH60.075	60	75			0,486	1		STK
-	ZMVH60.100	60	100			0,533	1		STK
-	ZMVH60.150	60	150			0,659	1		STK
-	ZMVH60.200	60	200			0,824	1		STK
-	ZMVH60.300	60	300			1,385	1		STK
-	ZMVH60.400	60	400			2,042	1		STK
-	ZMVH60.500	60	500			2,913	1		STK
-	ZMVH60.600	60	600			3,938	1		STK

Nombre minimal des boulons et des écrous: 4 pièces.