


ASTFCL

Aftakstuk 90°



Gesloten bodem
Boordomslag

Stand. Uitv.


Sendzimir

Mat. Opt.

Hot-Dip

HD Artikel	↑ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD ASTFCL60.100	60	100	2		1,030	1		STK
HD ASTFCL60.150	60	150	2		1,480	1		STK
HD ASTFCL60.200	60	200	2		1,980	1		STK
HD ASTFCL60.250	60	250	2		2,620	1		STK
HD ASTFCL60.300	60	300	2		3,320	1		STK
HD ASTFCL85.100	85	100	2		1,230	1		STK
HD ASTFCL85.150	85	150	2		1,720	1		STK
HD ASTFCL85.200	85	200	2		2,290	1		STK
HD ASTFCL85.250	85	250	2		2,950	1		STK
HD ASTFCL85.300	85	300	2		3,680	1		STK
HD ASTFCL110.150	110	150	2		1,970	1		STK
HD ASTFCL110.200	110	200	2		2,580	1		STK
HD ASTFCL110.250	110	250	2		3,280	1		STK
HD ASTFCL110.300	110	300	2		4,050	1		STK


Te bevestigen met:



Koppelplaat
V85.200



Koppelplaat
V35.200



Koppelplaat
V60.200

Multifunctioneel aftakstuk dat ook gebruikt kan worden als T-stuk of Kruisstuk.

Geïntegreerde verbindingstukken voor potentiaal verbinding.