

HSMES

Enkele hangsteun



Hangsteunprofiel: MP41.41S
 Gelaste kopplaat: 135x135 mm

Stand. Uitv. Elektrolytisch verzinkt

Mat. Opt. Hot-Dip

HD Artikel	↕ mm	↔ mm	→ ← mm	↔ mm	kg/stk	📦	Stock	Eenh.
HD HSMES200	200	41			1,020	20	X	STK
HD HSMES300	300	41			1,280	1	X	STK
HD HSMES400	400	41			1,530	1	X	STK
HD HSMES500	500	41			1,790	1	X	STK
HD HSMES600	600	41			2,050	1	X	STK
HD HSMES800	800	41			2,570	1	X	STK
HD HSMES1000	1000	41			3,090	1	X	STK
HD HSMES1200	1200	41			3,600	1	X	STK
HD HSMES1500	1500	41			4,380	1	X	STK
- HDHSMES200	200	41			1,020	20	X	STK
- HDHSMES300	300	41			1,280	1	X	STK
- HDHSMES400	400	41			1,530	1	X	STK
- HDHSMES500	500	41			1,790	1	X	STK
- HDHSMES600	600	41			2,050	1	X	STK
- HDHSMES800	800	41			2,570	1	X	STK
- HDHSMES1000	1000	41			3,090	1	X	STK
- HDHSMES1200	1200	41			3,600	1	X	STK
- HDHSMES1500	1500	41			4,380	1	X	STK

Ook toe te passen voor dubbele montage.
 Glijmoer PNP10 en drukkbout B10.30 toepassen.
 Bescherm dop in gele PVC: DOP41.41.