



TFCL110S

TFCL met SIN



Te bevestigen met:



Koppelplaat
V85.200

Stand. Uitv.		Sendzimir							
Mat. Opt.		Hot-Dip							
HD Artikel		↕ mm	↔ mm	→ ← mm	↔ mm	kg/m	📦	Stock	Eenh.
HD TFCL110.150.200S12		110	150	2	3000	6,840	30		M
HD TFCL110.150.200S13		110	150	2	3000	6,840	30		M
HD TFCL110.150.200S23		110	150	2	3000	7,660	30		M
HD TFCL110.200.200S12		110	200	2	3000	7,640	30		M
HD TFCL110.200.200S13		110	200	2	3000	7,640	30		M
HD TFCL110.200.200S23		110	200	2	3000	8,460	30		M
HD TFCL110.250.200S12		110	250	2	3000	8,440	30		M
HD TFCL110.250.200S13		110	250	2	3000	8,440	30		M
HD TFCL110.250.200S23		110	250	2	3000	9,260	30		M
HD TFCL110.300.200S12		110	300	2	3000	9,240	30		M
HD TFCL110.300.200S13		110	300	2	3000	9,240	30		M
HD TFCL110.300.200S23		110	300	2	3000	10,060	30		M

S12: 1 scheidingsschot in het midden van de kabelgoot
S13: 1 scheidingsschot op 1/3 van de rand van de kabelgoot
S23: 2 scheidingsschotten op 1/3 van de rand van de kabelgoot